

LOW CURRENT HIPOT TESTERS

Model	Test Type	Max Voltage	Max Current	Arc Detection Test	Arc Detection Defeatable	Leakage Test	Leakage Defeatable	Ground Continuity Test	Ground Continuity P/F Setting	Ground Continuity Defeatable	Ramp Time Range	Ramp Time Defeatable	Test Time Range	Test Time Defeatable	Display	Build in Portable Case	Dimmensions WxHxD	Aprox. Weight (lbs)
HT-2000P V2	AC	2000V	20mA	YES	NO	YES	NO	YES	2.93Ω	YES	1-5s	NO	1-60s	NO	4 Digit LED	NO	9" x 4" x 10"	11
HT-2000S	AC	2000V	20mA	YES	NO	YES	NO	YES	0.08-1.50Ω	YES	1-5s	NO	1-60s	NO	4 Digit LED	NO	9" x 4" x 10"	11
HT-2800P V2	DC	2800V	5mA	YES	NO	YES	NO	YES	2.93Ω	YES	1-5s	NO	1-60s	NO	4 Digit LED	NO	9" x 4" x 10"	11
HT-2800P V2-RF	DC	2800V	5mA	YES	NO	YES	NO	YES	2.93Ω	YES	1-5s	NO	1-60s	NO	4 Digit LED	YES	18.6" x 8.4" x 16.3"	22
HT-2800S	DC	2800V	5mA	YES	NO	YES	NO	YES	0.08-1.50Ω	YES	1-5s	NO	1-60s	NO	4 Digit LED	NO	9" x 4" x 10"	11
HT-3000P V2	AC DC	2000V 2800V	20mA 5mA	YES	NO	YES	NO	YES	2.93Ω	YES	1-5s	NO	1-60s	NO	4 Digit LED	NO	9" x 4" x 10"	11
HT-3000S	AC DC	2000V 2800V	20mA 5mA	YES	NO	YES	NO	YES	0.08-1.50Ω	YES	1-5s	NO	1-60s	NO	4 Digit LED	NO	9" x 4" x 10"	11
HT-3500S-RF	AC DC	2500V 3500V	20mA 5mA	YES	NO	YES	NO	YES	0.08-1.50Ω	YES	1-5s	NO	1-60s	NO	4 Digit LED	YES	18.6" x 8.4" x 16.3"	22
HT-4200S	AC DC	3000V 4200V	10mA 5mA	YES	NO	YES	NO	YES	0.08-1.50Ω	YES	1-5s	NO	1-60s	NO	4 Digit LED	NO	9" x 4" x 10"	11
HT-5000P V2	AC DC	5000V 6000V	10mA 5mA	YES	YES	YES	NO	NO	NA	NA	1-5s	YES	1-60s	YES	4 Digit LED	NO	11" x 4" x 13"	18
HT-5000P AC/DC 20mA	AC DC	5000V 6000V	20mA 10mA	YES	YES	YES	NO	NO	NA	NA	1-5s	YES	1-60s	YES	4 Digit LED	NO	17" x 6" x 17"	32
HT-10000P AC	AC	10,000V	10mA	YES	YES	YES	NO	NO	NA	NA	1-5s	YES	1-60s	YES	4 Digit LED	NO	11" x 4" x 13"	18
HT-10000P DC	DC	14,000V	5mA	YES	YES	YES	NO	NO	NA	NA	1-5s	YES	1-60s	YES	4 Digit LED	NO	11" x 4" x 13"	18
HT-10000P AC/DC	AC DC	10,000V 14,000V	10mA 5mA	YES	YES	YES	NO	NO	NA	NA	1-5s	YES	1-60s	YES	4 Digit LED	NO	17" x 6" x 17"	32
HT-10000P AC-01	AC	10,000V	20mA	YES	YES	YES	NO	NO	NA	NA	1-5s	YES	1-60s	YES	4 Digit LED	NO	17" x 6" x 17"	35

HIGH CURRENT HIPOT TESTERS

Model	Test Type	Max Voltage	Max Current	Arc Detection Test	Arc Detection Defeatable	Leakage Test	Leakage Defeatable	Ground Continuity Test	Ground Continuity P/F Setting	Ground Continuity Defeatable	Ramp Time Range	Ramp Time Defeatable	Test Time Range	Test Time Defeatable	Display	Build in Portable Case	Dimmensions WxHxD	Weight (lbs)
HT-5000P AC 200mA	AC	5000V	200mA	YES	YES	YES	NO	NO	NA	NA	1-5s	YES	1-60s	YES	4 Digit LED	NO	17" x 11" x 17"	66
HT-5000P AC/DC 200mA	AC DC	5,000V 7,000V	200mA	YES	YES	YES	NO	NO	NA	NA	1-5s	YES	1-60s	YES	4 Digit LED	NO	17" x 11" x 17"	90
HT-5000P AC/DC 200mA-TD	AC DC	5,000V 7,000V	200mA	YES	YES	YES	NO	NO	NA	NA	Auto	NA	1-90s	YES	7" Color Touchscreen	NO	22" x 27" x 26"	
HT-3000P AC 1A V2	AC	3000V	1A	YES	NO	YES	NO	NO	NA	NA	Manual	NA	1-60s	YES	4 Digit LED	NO	24" x 30" x 23"	160