



MegaPulse

1.2x50-12PF 39

PN:00-MP1.2x50-12PF 39 or 00-MP1.2x50-12PF 39

❖ 1.2x50 Waveform with 12Ω or 39Ω output impedance, 400-12kV.



Surge Tester with a 1.2us Rise Time x 50us Duration Time Waveform. Power supply will deliver a pulse derived from a capacitor charged to 12kV.

Digital Voltage knob with a 3 second charge time.

The front panel meter displays the voltage output.

- IEC 60060 sec 6, fig6.
- IEC 60335-1 chap 14 table 6.
- IEC 61180-1 Sec 6.
- IEC 61180-2 Sec 7.
- IEC 60065 Annex K, Fig 7b (option).
- UL 60950 Annex N (option).

*Actual products may vary depending on options and configuration.

➤ Features

- Digital output voltage knob on the front panel.
- Integrated High Voltage on hold circuit.
- External interlock disables HV output and defeats test when circuit is open.
- Microcontroller technologies.
- Front panel indicates internal HV and polarity.
- Polarity button selector on the front panel.
- Up to 12kV peak output.
- Optional USB TestMinder, computer control with auto-trigger.
- Leads, manual and calibration certificate included.
- One year calibration cycle
- One year warranty.



➤ Specifications

TESTING CIRCUITRY

Output Peak:	400V-12kV ±3%.
Open Circuit Rise Time:	1.2us, ±30% (Trise=1.67*(T90%-T30%) per IEC 1180.
Open Circuit Duration Time:	50us, ±20% (Time to half-value) per IEC 1180.
Virtual Impedance:	12Ω or 39Ω.
Current Waveform:	Not defined.
Short Peak Current:	1000A for 12Ω output testers. 300A for 39Ω output testers.

CONTROL

Voltage Control:	Manually, Digital knob on the front panel or via optional USB TestMinder.
Polarity Control:	Pos. and Neg. Alternating control on front panel or via optional USB TestMinder.
Charge:	Control on front panel or via optional USB TestMinder.
Trigger:	Control on front panel or via optional USB TestMinder.
Remote Control:	Optional wired remote control, 20ft long, controls, Trigger, Charge, and Polarity.

DISPLAY

Voltage Display:	5 Digit LED Display.
Voltage Meter resolution:	5V.
Voltage Meter Accuracy:	400 to 999V ±10V, 1000 to 12kV ±50V.
Display Reads:	Output Voltage. (Not bulk cap).

OPERATION

Duty Cycle:	30s between pulses 6kV max, 60s between pulses 12kV.
Charge Time:	<3s.
Time between pulses:	Adjustable via USB TestMinder software.

ELECTRICAL

Line Voltage:	120V AC, 50/60Hz. Optional 100, 110, 220, 230 and 240V.
---------------	---

SAFETY

Safety Interlock	2-pin terminal block on rear panel; shorted for operation.
------------------	--

OUTPUTS - FRONT

OUTPUT:	High Voltage insulated socket.
RETURN:	High Voltage insulated socket.

OUTPUTS - REAR

TESTMINDER:	DB9 Female (Optional).
SAFETY INTERLOCK:	2-pin Terminal Block.
Inlet Module:	Inlet module with fuse and power switch combination.

➤ Environmental

Operating Temperature:	15-28 °C.
Relative Humidity Range:	0-90% non-condensing.



➤ General

Dimensions:	17" wide x 6U high x 17" deep.
Weight:	40 lbs. approx.
Product Package:	<ul style="list-style-type: none">• Megapulse 1.2x50-12PF Tester.• Megapulse 1.2x50-12PF User Manual.• High Voltage Test Leads Qty 1 (Red end), Qty 1 (Black end)• NIST traceable calibration certificate to ANSI Z540• Calibration waveforms

➤ Options

00-MP220, MP230, MP240:	220V, 230V or 240V mains tester operation available.
00-TMM-PF	TestMinder Computer Control.
00-RI	Relay Interface Control.
00-CASE-9U:	Pelican Case with foam.
A2LA-TECH-MP	ISO17025 Calibration
950-12; 950-39	Provides test capability to IEC60065 Annex K Line 2 and UL60950 Annex N Line 2.

Rev 2.0

